

Marine Hose

Marine Hose



MXH

MARINE EXHAUST HARD WALL

Product Information:

All hoses made to USCG specifications. Recommended for working temperatures of up to 100°C (212°F). Used for wet exhaust in pleasure craft marine engine applications. Specially blended EPDM tube and cover for long life under severe conditions. Black tube and cover with blue stripe.

Construction:

Tube - EPDM rubber

Reinforcement - Multiple layer synthetic yarn

Cover - EPDM rubber

Branding - Blue stripe "CERTIFIED MARINE EXHAUST size"

Temperature Range:

-40°C to +100°C (-40°F to +212°F)

Standard Lengths:

100ft cut to any length at no charge

Parts No.	I.D. Inches	O.D. Inches	Bend Radius(In.)	Approx. Wt. Per. Ft. Lbs.
MXH-.5	1/2	0.84	4	0.35
MXH-.625	5/8	1.03	5	0.40
MXH-.75	3/4	1.16	6	0.45
MXH-.875	7/8	1.25	7	0.50
MXH-1	1	1.40	8	0.60
MXH-1.125	1-1/8	1.52	9	0.70
MXH-1.25	1-1/4	1.70	10	0.75
MXH-1.5	1-1/2	1.97	12	0.90
MXH-1.625	1-5/8	2.10	13	1.05
MXH-1.75	1-3/4	2.23	14	1.20
MXH-1.875	1-7/8	2.35	15	1.25
MXH-2	2	2.50	16	1.35
MXH-2.125	2-1/8	2.64	17	1.45
MXH-2.25	2-1/4	2.75	18	1.55
MXH-2.375	2-3/8	2.88	19	1.65
MXH-2.5	2-1/2	3.06	20	1.80
MXH-2.625	2-5/8	3.18	21	1.90
MXH-2.875	2-7/8	3.43	23	2.10
MXH-3	3	3.61	24	2.25
MXH-3.125	3-1/8	3.64	25	2.30
MXH-3.5	3-1/2	4.11	28	2.65
MXH-4	4	4.56	32	3.20
MXH-4.125	4-1/8	4.68	33	3.30
MXH-4.5	4-1/2	5.19	36	3.71
MXH-5	5	5.59	40	4.02
MXH-5.5	5-1/2	6.09	44	4.51
MXH-6	6	6.61	48	5.00

