

Sewer Cleaning Hose



SP

SP PIRANHA SEWER CLEANING HOSE

Application:

Piranha hose is constructed from materials selected to provide rugged and reliable service under even the most severe and demanding conditions found in high pressure sewer cleaning.

Construction:

Tube - Yellow olefin
Reinforcement - Single high tensile braid
Cover - Orange polyether-urethane

Temperature Range:

-40°C to +50°C (-40°F to +122°F)

Parts No.	I.D. Inches	O.D. Inches	Max W.P. PSI	Min B.P. PSI	Bend Radius Inches	Cover Thickness	Approx. Wt. Per. Ft. Lbs.	Reel Length Ft.
SP-16-500R	1	1.460	2500	6250	6	0.065	0.400	500
SP-16-600R	1	1.460	2500	6250	6	0.065	0.400	600

Each length comes with a male NPT attached each end; female swivel on one end is also available by special order.



HP

HP PIRANHA SEWER CLEANING HOSE

Application:

Piranha hose is constructed from materials selected to provide rugged and reliable service under even the most severe and demanding conditions found in high pressure sewer cleaning.

Construction:

Tube - Yellow olefin
Reinforcement - Double high tensile braid
Cover - Blue polyether-urethane

Temperature Range:

-40°C to +50°C (-40°F to +122°F)

Parts No.	I.D. Inches	O.D. Inches	Max W.P. PSI	Min B.P. PSI	Bend Radius Inches	Cover Thickness	Approx. Wt. Per. Ft. Lbs.	Reel Length Ft.
HP-16-600R	1	1.475	3000	7500	8	0.500	0.410	600

Each length comes with a male NPT attached each end; female swivel on one end is also available by special order.

The use of end fittings and assembly tooling other than that supplied by Piranha Hose Products is at the risk of the users.