



Grain Vac Hose



Mississauga

Ph: 905-670-5700 / 800-387-9537

Fx: 905-670-3700

Email: sales@irprubber.com

Edmonton

Ph: 780-485-1227

Fx: 780-485-1228

Email: saleswest@irprubber.com

Vancouver

Ph: 604-472-1200 / 877-527-1200

Fx: 604-472-1201

Email: saleswest@irprubber.com

Visit us at [**www.irprubber.com**](http://www.irprubber.com)



Grain Vac Hose

I.D.	Working Pressure (PSI at 72°F/22°C)	Vacuum (in Hg at 72°F/22°C)	Bend Radius	O.D. Nominal	Weight (lbs. per Ft.)
4"	30	20	6"	4.5"	0.87
5"	24	14	6.3"	5"	1.02
6"	24	12	6.5"	6.7"	1.21
7"	21	10	7.5"	7.7"	1.41
8"	22	8	8.5"	8.7"	1.83

PART No.	DESCRIPTION
GRAINVAC-4	4" ID FLEX TUBE PU 60 HIGH FLEX
GRAINVAC-5	5" ID FLEX TUBE PU 60 HIGH FLEX
GRAINVAC-6	6" ID FLEX TUBE PU 60 HIGH FLEX
GRAINVAC-7	7" ID FLEX TUBE PU 60 HIGH FLEX
GRAINVAC-8	8" ID FLEX TUBE PU 60 HIGH FLEX

PART No.	DESCRIPTION
GRAINVAC-ST-4	4" ID FLEX TUBE PU 60 HIGH FLEX W/ static wire
GRAINVAC-ST-5	5" ID FLEX TUBE PU 60 HIGH FLEX W/ static wire
GRAINVAC-ST-6	6" ID FLEX TUBE PU 60 HIGH FLEX W/ static wire
GRAINVAC-ST-7	7" ID FLEX TUBE PU 60 HIGH FLEX W/ static wire
GRAINVAC-ST-8	8" ID FLEX TUBE PU 60 HIGH FLEX W/ static wire

- Ultra smooth interior for maximum flow characteristics
 - Excellent abrasion and wear resistance
 - Great low temperature flexibility
 - .060" wall thickness
 - Crush resistant
 - Standard lengths: 50'
- Heavyweight coextruded ether based polyurethane hose with rigid external ABS Helix
 - -40°F to 200°F (-40°C to 93°C)

Visit us at www.irprubber.com