



INDUSTRIAL HOSE

*MINE MAXX - STEEL MAXX - FLOW MAXX - PETRO MAXX
POLAR MAXX - FOOD MAXX - CHEM MAXX - STEAM MAXX
CMC MAXX - BULK MAXX - BLAST MAXX - CEMENT MAXX*

***ENGINEERED FOR...
MAXX QUALITY. MAXX VALUE.***

MAXX MINE MAXX 400 PSI Air Hose (ESY)

Application:

MINE MAXX is a premium heavy duty 400 PSI air hose designed for the most harsh mining, construction and industrial applications. This mandrel built hose is designed with an extra heavy duty cover to give maximum resistance to abrasion.

Construction:

Tube - Smooth black oil mist resistant synthetic rubber
Reinforcement - Multiple layers of high tensile spirally wound synthetic yarn
Cover - Yellow weather, cut and abrasion resistant synthetic rubber
Branding - Blue stripe **MAXX MINE MAXX 400 PSI HOSE**

Temperature Range:

-40°C to +82°C (-40°F to +180°F)

Size Range:

1/2" - 4"



MAXX STEEL MAXX WIRE REINFORCED AIR HOSE (WRY)

Application:

STEEL MAXX is a mandrel built wire reinforced heavy duty air hose for high pressure pneumatic applications. Built to withstand severe external abuse including mining, construction and industrial use.

Construction:

Tube - Black oil and heat resistant SBR/NBR rubber
Reinforcement - Layers of high tensile steel wire
Cover - Yellow cut and gouge resistant synthetic rubber
Branding - Red stripe **MAXX STEEL MAXX WIRE REINFORCED AIR**

Temperature Range:

-30°C to +82°C (-22°F to +176°F)

Size Range:

1/2" - 4"



MAXX FLOW MAXX EPDM WATER DISCHARGE HOSE (CWD)

Application:

FLOW MAXX is a medium duty multi-use EPDM water discharge hose used on construction sites and for general water service.

Construction:

Tube - Black EPDM rubber blend
Reinforcement - Multiple spirals of synthetic yarn
Cover - Black EPDM rubber blend
Branding - Yellow stripe **MAXX FLOW MAXX EPDM WATER DISCHARGE HOSE**

Temperature Range:

-32°C to +82°C (-25°F to +180°F)

Size Range:

1-1/4" - 12"



MAXX FLOW MAXX EPDM WATER SUCTION HOSE (WS)

Application:

FLOW MAXX EPDM water suction hose is a heavy duty rubber hose that is excellent for construction, quarries, and general use. Suitable for full vacuum.

Construction:

Tube - Black EPDM rubber blend
Reinforcement - A high tensile steel helix embedded between textile cords
Cover - Black EPDM rubber blend
Branding - Green stripe **MAXX FLOW MAXX EPDM WATER SUCTION HOSE**

Temperature Range:

-32°C to +82°C (-25°F to +180°F)

Size Range:

3/4" - 12"



MAXX PETRO MAXX PETRO MAXX TANK TRUCK 150 PSI (TT)

Application:

PETRO MAXX is an all purpose petroleum suction and discharge hose used for gasoline, distillate, kerosene, diesel, oil suspensions, emulsions and other petroleum products with up to a maximum of 50% aromatic content. Also used as a hydraulic suction return line and is suitable for full vacuum service.

Construction:

Tube - Smooth black nitrile rubber for maximum oil resistance
Reinforcement - A heavy wire helix embedded between layers of synthetic high tensile textile cords
Cover - Smooth black oil, weather and abrasion resistant nitrile rubber/PVC blend
Branding - Blue stripe **MAXX PETRO MAXX TANK TRUCK 150 PSI**

Temperature Range:

-35°C to +82°C (-31°F to +180°F)

Size Range:

3/4" - 6"



MAXX POLAR MAXX LOW TEMP TANK TRUCK 150 PSI (TT-LT)

Application:

POLAR MAXX is an all purpose petroleum suction and discharge hose designed to remain flexible in low temperature conditions. The corrugated cover makes the hose very flexible and it is also suitable for full vacuum service.

Construction:

Tube - Smooth black low temp nitrile for maximum oil resistance
Reinforcement - Dual wire helix embedded between layers of synthetic high tensile textile cords
Cover - Blue corrugated oil resistant rubber which is specially formulated to remain flexible in low temperatures
Branding - Red stripe **MAXX POLAR MAXX LOW TEMP TANK TRUCK 150 PSI**

Temperature Range:

-51°C to +82°C (-60°F to +180°F)

Size Range:

1" - 4"



MAXX FOOD MAXX FDA FOOD SUCTION HOSE 250 PSI (WF)

Application:

FOOD MAXX FDA is a premium quality food suction and discharge hose and is designed to handle most liquid food products including fats and oils without imparting taste, odour, or smell. FOOD MAXX'S nitrile cover has excellent resistance to natural oils and is suitable for full vacuum service.

Construction:

Tube - White nitrile, non-toxic, FDA approved
Reinforcement - A steel helix embedded between layers of synthetic cords
Cover - Grey oil and fat resistant nitrile rubber
Branding - Red stripe **MAXX FOOD MAXX FDA FOOD SUCTION 250 PSI**

Temperature Range:

-35°C to +93°C (-31°F to +200°F)

Size Range:

1-1/2" - 4"



MAXX CHEM MAXX XLPE CHEMICAL HOSE 150 PSI (AC)

Application:

CHEM MAXX is a very versatile hose used for the transfer of chemicals and will handle 90% of known chemicals and petroleum products in both suction and discharge applications.

Construction:

Tube - Translucent smooth cross-lined polyethylene (XLPE)
Reinforcement - A heavy wire helix between two layers of high tensile synthetic cords
Cover - Green smooth EPDM chemical resistant rubber
Branding - White stripe **MAXX** CHEM MAXX XLPE CHEMICAL HOSE 150 PSI

Temperature Range:

-29°C to +66°C (-20°F to +150°F)

Size Range:

3/4" - 4"



MAXX STEAM MAXX CHLOROBUTYL STEAM HOSE (WRSC)

Application:

STEAM MAXX's tube is formulated of chlorobutyl rubber giving it superior resistance to heat aging and improved life expectancy. This extremely flexible hose is designed for transfer of steam up to 250 PSI and 22°C (430°F) in petrochemical plants, shipyards, oil fields and other industrial applications.

Construction:

Tube - Black CHLOROBUTYL rubber, compounded to resist heat aging
Reinforcement - Layers of high tensile steel wire
Cover - Red abrasion & heat resistant EPDM rubber (pin pricked)
Branding - Yellow stripe **MAXX** STEAM MAXX CHLOROBUTYL STEAM HOSE 250 PSI (17 BAR) 430°F (221°C) - DRAIN AFTER USE

Temperature Range:

-40°C to +221°C (-40°F to +430°F)
intermittent to 232°C (450°F)

Size Range:

3/4" - 2"



MAXX STEAM MAXX EPDM STEAM HOSE (WRS)

Application:

STEAM MAXX EPDM is an extremely flexible hose for use with steam at temperatures up to 208°C (406°F). Not suitable for superheated steam.

Construction:

Tube - Black EPDM Rubber, compounded to resist heat aging
Reinforcement - Layers of high tensile steel wire
Cover - Red abrasion & heat resistant EPDM rubber
Branding - (Embossed) **STEAM MAXX EPDM 17 BAR (250 PSI) 208°C (406°F) SATURATED STEAM ONLY - DRAIN AFTER USE**

Temperature Range:

-40°C to +208°C (-40°F to +406°F)

Size Range:

1/2" - 2"



MAXX CMC MAXX CORRUGATED MATERIAL CONDUCTING HOSE (CMC)

Application:

CMC MAXX corrugated material handling hose is designed for abrasive suction and discharge service. Utilizes split flanged couplings, which can be installed without special tools, allows hose to be purchased in long lengths and cut as required. The reusable coupling allows full flow of material and permits the hose to be easily rotated for even wear.

Construction:

Tube - Highly abrasion resistant red pure gum rubber
Reinforcement - Synthetic fabric reinforcement and wire helix
Cover - Black abrasion resistant synthetic rubber corrugated to enhance flexibility and match internal corrugations of external split flanged coupling
Branding - Red stripe **MAXX** CMC MAXX CORRUGATED MATERIAL HANDLING CONDUCTING HOSE

Temperature Range:

-40°C to +71°C (-40°F to +160°F)

Size Range:

2" - 12"



MAXX BULK MAXX TAN BULK MATERIAL HANDLING HOSE (TB)

Application:

BULK MAXX Tan Bulk Material Handling hose is used in the transfer of dry non-oily abrasive materials such as sand, limestone, plastic pellets, sugar, corn, etc. Suitable for full vacuum.

Construction:

Tube - Tan natural rubber smooth abrasion resistant, 3/16" thick (FDA approved)
Reinforcement - A high tensile steel helix embedded between textile cords
Cover - Tan, natural rubber corrugated for flexibility, non marking
Branding - Blue stripe **MAXX** BULK MAXX TAN BULK MATERIAL

Temperature Range:

-35°C to +82°C (-31°F to +180°F)

Size Range:

2" - 6"



MAXX BLAST MAXX SANDBLAST HOSE 150 PSI (SB)

Application:

BLAST MAXX Sandblast Hose is designed for conveying sand, steel shot and other abrasive materials. Built with a static conductive 1/4" thick abrasion resistant tube designed for transferring abrasives at high velocity.

Construction:

Tube - 1/4" black static conductive abrasion resistant natural rubber
Reinforcement - Two layers of synthetic textile cords
Cover - Black natural / EPDM blended rubber
Branding - Blue stripe **MAXX** BLAST MAXX SANDBLAST HOSE 150 PSI

Temperature Range:

-35°C to +82°C (-31°F to +180°F)

Size Range:

1/2" - 3"



MAXX CEMENT MAXX-S BULKMASTER DISCHARGE (BMS) **MAXX** CEMENT MAXX-H BULKMASTER HARDWALL SUCTION (BMH)

Application:

CEMENT MAXX-S and CEMENT MAXX-H are material handling hoses with an abrasion resistant tube and are used for the conveying, dry bulk products including chalk, china clay, limestone, ground silica, fullers earth, dry cement, sodium sulphate, lime and fertilizer.

Construction:

Tube - Black abrasion resistant natural rubber. Available in different gauges
Reinforcement - A high tensile helix embedded between textile cords hardwall (softwall - no wire)
Cover - Black abrasion and weather resistant synthetic rubber
Branding - Green stripes **MAXX** CEMENT MAXX-S and **MAXX** CEMENT MAXX-H BULKMASTER DISCHARGE AND SUCTION

Temperature Range:

-35°C to +82°C (-31°F to +180°F)

Size Range:

3" - 4 - 1/2"





www.irprubber.com

MISSISSAUGA LOCATION

6300 Edwards Blvd., Unit 1, Mississauga, ON L5T 2V7

P: 905.670.5700 ▲ F: 905.670.3700 ▲ T: 1.800.387.9537 ▲ E: sales@irprubber.com

EDMONTON LOCATION

5724 - 67th Ave. NW, EDMONTON, AB T6B 3P8

P: 780.485.1227 ▲ F: 780.485.1228

VANCOUVER LOCATION

1525 Broadway Street, Unit 120, Port Coquitlam, BC V3C 6P6

P: 604.472.1200 ▲ F: 604.472.1201 ▲ T: 1.877.527.1200 ▲ E: saleswest@irprubber.com