

Flexaust Hose & Ducting



FLX-SD

FLX-THANE SD STATIC DISSIPATIVE POLYURETHANE

Colour:

Clear or Black

Temperature Range:

-54°C to +107°C (-65°F to +225°F)

Stock Sizes:

None

Available Sizes:

2" - 12"

Standard Stock Sizes:

None

Non Standard Lengths:

Made to order

FLX-THANE SD - A durable urethane hose has excellent resistance to abrasion, cutting and gouging. Medium weight ether-type, static dissipative polyurethane wall. Supported by a bronze coated spring steel wire helix for crush resistance and efficient flow characteristics. Suitable for chemical fume exhausting, lightweight material handling, and dust collection applications. Ideal for applications where static electricity is present. Clear is manufactured with FDA acceptable materials.

Wall Thickness = .030"

Parts No.	I.D. Inches	Weight (lbs./ft.)	Positive Pressure PSI	Negative Pressure IN.HG	Centerline Bend Radius, Inches
FLX-BSD-2	2	.25	30	29	2.00
FLX-BSD-3	3	.40	29	29	3.00
FLX-BSD-4	4	.70	25	29	4.00
FLX-BSD-6	6	1.00	19	15	6.00
FLX-BSD-8	8	1.50	14	9	8.00
FLX-BSD-10	10	1.60	11	4	8.00
FLX-BSD-12	12	2.00	10	2.2	10.00
FLX-CSD-2	2	.25	30	29	2.00
FLX-CSD-3	3	.40	29	29	3.00
FLX-CSD-4	4	.70	25	29	4.00
FLX-CSD-6	6	1.00	19	15	6.00
FLX-CSD-8	8	1.50	14	9	8.00
FLX-CSD-10	10	1.60	11	4	8.00
FLX-CSD-12	12	2.00	10	2.2	10.00

*Pressures based on straight lengths of hose @ 72° F.